TABLE OF CONTENTS

	20161912	Раде
ACKNOWI	EDGEMENTS	iii
THAI ABST	TRACT	V
ABSTRACT		vi
TABLE OF	CONTENTS	viii
LIST OF FI	GURES	xi
CHAPTER	I INDRODUCTION	1
5011.	Background	2. 1
1.2.	Problem Statement	2
1.3.	Significance of Research	3
1.4.	Research Objectives	3
1.5.	Scope of Research	3
1.6.	Outline of the Thesis	4
CHAPTER	II LITERATURE REVIEW	6
2.1.	Review of Four-Way Hot Box Designed by Karno (2008)	6
	2.1.1. The Four-Way Hot Box Design	6
	2.1.2. The Four-Way Hot Box Construction	10
ົລິມສິກອິ	2.1.3. The Four-Way Hot Box Operation	12
CIOCIIIC	2.1.4. The Four-Way Hot Box Result	14
Copyri2.2.h	Criticize of the Four-Way Hot Box Test	rsi8
	2.2.1. Criticize of the Design	18
	2.2.2. Criticize of the Construction	18
	2.2.3. Criticize of the Operation Work	23
	2.2.4. Criticize of the Results	23

2.3. Reliability	of a Research Tool	24
2.4. Summary o	f the Previous Four-Way Hot Box Test Arguments	25
2.5. Limitation	of Thesis Research	27
2.6. Temperatur	e in Thailand	28
CHAPTER III RESEAF	CH OBJECTIVES AND METHODOLOGY	30
3.1. Research O	bjectives	30
3.2. Research P	rocess and Tools	31
3.3. Review of t	he Comparative Hot Box Test Method	33
3.4. Experiment	al Arrangement	36
3.4.1. Tes	ing Samples	36
3.4.2. Mea	surement Tools	36
3.4.3. Ro	om Arrangement and Temperature Control	38
CHAPTER IV EXPERI	MENT AND RESULT	39
4.1. The Investi	gation of Room Temperature	39
4.1.1. Purj	pose and Studied Parameter	39
4.1.2. Spe	cimens	41
4.1.3. Pro	redure	41
4.1.4. Tes	ing Results	43
4.1.5. Ana	lysis of Testing Results	50
4.2. The Investi	gation of Starting Ambient Temperature	53
4.2.1 Purj	oose and Studied Parameter	53
4.2.2. Spe	cimens	55
Copyright4.2.3. Pro	edure Chiang Mai Univers	55
4.2.4. Tes	ing Results	56
4.2.5. Ana	lysis of Testing Results	65

4.3.	Additional Investigation:		
	The Investigation of Heating Temperature	69	
	4.3.1. Purpose and Studied Parameter	69	
	4.3.2. Specimens	69	
	4.3.3. Procedure	70	
	4.3.4. Testing Results	71	
9	4.3.5. Analysis of Testing Results	73	
CHAPTER V	CHAPTER V DISCUSSION AND CONCLUSION		
5.1.	Discussion	76	
372	5.1.1. The Room Temperature	76	
Z PE	5.1.2. The Starting Ambient Temperature	77	
0 0 6	5.1.3. The Heating Speed	77	
Q	5.1.4. The Testing Periods	77	
5.2.	Conclusion	78	
REFERENC	ES	79	
CURRICULUM VITAE		82	
	M. RSY		
	A INTVER		

ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่ Copyright[©] by Chiang Mai University All rights reserved

LIST OF FIGURES

Figure	ુ ગારા દા છે ?	Page
2.1	Schematic of a Generic Enclosure with Single ABE	
	Wall System, (Van Dessel et al., 2004)	8
2.2	Principles Solar Heat Test-Cell System along summer	
	and winter periods, (Ahmad et al., 2005)	8
2.3	Top view outline of all heating and metering cells prepared	
502	for testing (X: thermometer positions) (Karno, 2008)	9
2.4	Section view (A-A) of heating and metering cells and test	
Q	specimens (X: thermometer positions) (Karno, 2008)	10
2.5	The Hot box assembly	11
2.6	A 200-W light bulb and dimmer-switch controller	12
2.7	Thermometer-Sensors and Thermo-Gun	14
2.8	Air temperatures in metering cells when heating cell	
	was heated up to 50°C	15
2.9	Air temperatures in metering cells when heating cell	
ດິມສິກຄິ	was heated up to 55°C	16
	Air temperatures in metering cells when heating cell	INIJ
Copyright	was heated up to 60°C ang Mai Unive	rsi7ty
2.11	Direction of heat exchanged (Q in and Q out)	
	of the four-way hot box on section view (A-A) of	e u
	heating and metering cells between the test specimens	21

2.12	Annual means minimum temperatures in Thailand	
	(1951 – 2009), source from TMD, (2010)	29
2.13	Annual means maximum temperatures in Thailand	
	(1951 – 2009), source from TMD, (2010)	29
3.1	Research Procedure	32
3.2	Two types of thermometers sensor, and a thermo gun	37
3.3	A heater and an air conditioner	38
4.1	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
	and heating cell in morning test of natural room temperature	
502	from 19 to 25 °C	44
4.2	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
Q	and heating cell in afternoon test of natural room temperature	
Ē	from 25 to 30 °C	45
4.3	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
	and heating cell at night test of natural room temperature	
	from 30 to 24 °C	46
4.4	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
	and heating cell of constant room temperature of 19 °C	47
S 2 3 9 4.5	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	1811
qualib	and heating cell of constant room temperature of 25 °C	48
Copyrig ^{4.6} t	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	sity
Allr	and heating cell of constant room temperature of 30 °C	⁴⁹ d

4.7	Comparison of 1, 2, 3, 4, 5 inches EPS samples between	
	constant room temperature & natural room temperature tests	
	with a similarity of ambient temperature of 19 °C	50
4.8	Comparison of 1, 2, 3, 4, 5 inches EPS samples between	
	constant room temperature & natural room temperature tests	
	with a similarity of ambient temperature of 25 °C	51
4.9	Comparison of 1, 2, 3, 4, 5 inches EPS samples between	
6	constant room temperature & natural room temperature tests	
	with a similarity of ambient temperature of 30 °C	52
5 4.10	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
208-	and heating cell with the starting ambient temperature	
Q	of 18 °C	57
4.11	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
	and heating cell with the starting ambient temperature	
	of 20 °C	58
4.12	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
	and heating cell with the starting ambient temperature	
	of 22 °C	59
4.13	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	121
aoang	and heating cell with the starting ambient temperature	n
Copyright	of 24 °C by Chiang Mai Univer	60
4.14	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
	and heating cell with the starting ambient temperature	e (
	of 26 °C	61

4.15	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
	and heating cell with the starting ambient temperature	
	of 28 °C	62
4.16	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
	and heating cell with the starting ambient temperature	
	of 30 °C	63
4,17	Air-temperature of 1, 2, 3, 4 and 5 inches EPS samples	
6	and heating cell with the starting ambient temperature	
	of 32 °C	64
502 4.18	Eight types of air temperature of heating cell with	
Silv	the variable of starting ambient temperature	
C	from 18°C to 32 °C	65
4.19	Eight types of air temperature of 1 inch EPS foam with	
E.	the variable of starting ambient temperature	
Ý.	from 18°C to 32 °C	66
4.20	Eight types of air temperature of 2 inches EPS foam with	
	the variable of starting ambient temperature	
	from 18°C to 32 °C	66
S 21 3 n 4.21	Eight types of air temperature of 3 inches EPS foam with	K1
COCHD	the variable of starting ambient temperature	
Copyright	from 18°C to 32 °C hiang Mai University	67
4.22	Eight types of air temperature of 4 inches EPS foam with	, P (
	the variable of staring ambient temperature	
	from 18°C to 32 °C	67

	4.23	Eight types of air temperature of 5 inches EPS foam with	
		the variable of starting ambient temperature	
		from 18°C to 32 °C	68
	4.24	Graphic result of air temperature of metering cells	
		and heating cell with 100% of a light bulb power	71
	4.25	Graphic result of air temperature of metering cells	
4		and heating cell with 70% of a light bulb power	72
	4.26	Comparison of graphic result of the test between 70%	
		and 100% of a light bulb power to reach up the maximum	
502		temperature of 60 °C in the heating cell	74
2021		The second second	
Í			

ลิขสิทธิ์มหาวิทยาลัยเชียงใหม่ Copyright[©] by Chiang Mai University All rights reserved

AI UNIVER